

TECHNICAL DATA SHEET

PROTEXX-LT™ SURFACE PROTECTION

TRAXX PROTEXX-LT™ SURFACE PROTECTION is flexible fiber paper engineered for temporary floor protection during construction and remodeling. This product is cost-effective and reusable.

SPECIFICATIONS:

- Recyclable and reusable
- Not acid free
- Does not meet any military specifications

FLOORS and SURFACES APPROVED:

Virtually all surfaces: concrete, stone, marble, terrazzo, wood, linoleum, tile, carpet (natural and synthetic), VCT, LVT, vinyl, epoxy, laminates and many more.

AVAILABLE SIZES — Part Number, Roll/Sheet Size:

- PSP-2035
- 20 MIL (± 1 MIL)
- Roll Size: 35" x 100' (88.9cm x 30.48m)

OTHER RELEVANT SPECS:

- Weight: 20 lbs per roll
- Area Coverage Per Roll: 291.66 square feet (27.1m²)
- Case Quantity (optional): 9 Rolls

WATER VAPOR TRANSMISSION: ASTM E 96 — 64.5 PERM

FLAME RATING: ASTM E 84 — Class A Index (flame / smoke)

INSTRUCTIONS:

Flooring must be free from dirt and debris. Vacuum or sweep floors to be covered. Roll out PROTEXX-LT™. Cut to desired length. Tape seams with TRAXX PROTEXX™ seam tapes.

PROTEXX-LT™ SURFACE PROTECTION should be stored in a dry, cool and well-ventilated away from open flame and other source of ignition. Follow good hygiene and safety practice. Avoid eye contact and do not breath dust.

