

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Resilient Edge Guard Mouldings

1.2. Manufacturer:

Tarkett
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkettna.com
E-mail: info@johnsonite.com

Phone: (800) 899-8916
(440) 543-8916

1.3. Proprietary Product Description:

1.3.1. **Construction:** Johnsonite Edge Guard Mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Johnsonite Edge Guard Mouldings are designed for interior applications only and not recommended for commercial kitchen environments.

1.3.2. Styles:

EG-XX-G *: 1-11/32" (3.41 cm) transition reducer with undercut for 5/16" (7.94 mm) glue down carpet, 2-3/8" (6.03 cm) base surface

EG-XX-H *: 1-9/32" (3.25 cm) transition reducer with undercut for 1/4" (6.35 mm) glue down carpet, 2-1/8" (5.40 cm) base surface

EG-XX-J *: 1-1/16" (2.70 cm) transition reducer with undercut for 3/16" (4.76 mm) glue down carpet, 1-3/4" (4.45 cm) base surface

EG-XX-K: Rounded top transition reducer with undercut for 1/4" (6.35 mm) carpet or artificial grass carpet, 1-5/8" (4.13 cm) base surface

EG-XX-L: Bevel-edge transition reducer with deep undercut for 5/16" (7.94 mm) carpet, 2" (5.08 cm) base surface

EG-XX-W: Bevel-edge transition reducer with undercut for 3/8" (9.53 mm) integral pad and carpet, 3" (7.62 cm) base surface

* Complies with ADA requirements for changes in level.

1.3.3. Physical Characteristics:

Length: 12 ft. (3.66 m)

Packaging: 20 pieces [240 ft. (73.15 m)] per carton

Note: EG-XX-L packaged 25 pieces per carton, 300 ft. (91.44 m).
EG-XX-W packaged 10 pieces per carton, 120' (36.58 m).

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Slip Resistance** (ASTM D 2047 Static Coefficient of Friction): Exceeds Federal Standards and ADA requirements of 0.5 SCOF for walking surfaces.

2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux): Class 1

3. INSTALLATION

3.1. See Johnsonite Resilient Moulding installation and maintenance instructions for complete details.

3.2. Adhesives:

Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)

Application: Brush on T-Moulding and track on mitered corner areas

Approximate coverage:

1 kg Unit (0.95 Qt) – 24 to 36 sq. ft.

6 kg Unit (1.44 Gal.) – 144 to 215 sq. ft.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Johnsonite Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.