

Style	Corner Guard*, Double Etched*, Effectual® Chair Rail, Etched*, Simple	Elegance
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	1/4" (6.35 mm)	3/16" (4.76 mm)
Profile	Smooth	Smooth
Profile Height	Corner Guard - 1" Double Etched, Etched, Simple - 4" or 4 1/4" Effectual® Chair Rail - 4" Etched - 6"	6"
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: IEQc2 - Low Emitting Materials	
mindful MATERIALS Manufacturing	Visit mM Origin website, mindfulmaterials.origin.build for current transparency information USA	
Warranty		
	Limited 5 Year Commercial Warranty	

Style	Cetera [®] , Flair [®] , Lunar, Simplicity [®]	Cache [®] , Etched, Iconic [®] , Marquee [®] , Regal [®] , Simple, Sophisticate [®]
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	5/16" (7.94 mm)	3/8" (9.52 mm)
Profile	Smooth	Smooth
Profile Height	Flair - 3" Cetera [®] , Lunar, Simplicity - 4" or 4 1/2" Simplicity - 6"	Cache [®] - 3" Illusion [®] - 3 1/4" Etched, Simple - 4" or 4 1/4" Cache [®] , Iconic [®] , Marquee [®] , Sophisticate [®] - 4 1/4" Regal - 5 1/4"
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v11-2010	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build for current transparency information	
Manufacturing	USA	
Warranty		
	Limited 5 Year Commercial Warranty	

Style	Quarter Round	*Pre-mitered Inside and Outside corners also available
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	1/2" (12.7 mm)	3/16" (4.76 mm)
Profile	Smooth	Smooth
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	Peel and Stick (No Adhesive Needed)	MR101 Acrylic
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v11-2010	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build for current transparency information	
Manufacturing	USA	
Warranty		
	Limited 5 Year Commercial Warranty	